


PCG-NV209

Model name

PCG-NV209

<i>Model number</i>	PCG-9C2M
<i>Operating system</i>	Microsoft® Windows® XP Home Edition
<i>Processor</i>	AMD Mobile Athlon™ XP processor 1800+ featuring PowerNow!™ Technology
<i>Hard disk drive</i>	30 GB
<i>Standard RAM</i>	256 MB DDR (in slot)
<i>Maximum RAM</i>	1 GB
<i>LCD screen</i>	15.0" XGA (1024x768) TFT screen
<i>L2 cache memory</i>	256 KB (on die)
<i>MPEG</i>	MPEG 2 Digital Video supports full-screen playback
<i>Graphics</i>	NVIDIA® GeForce4™ 420 Go graphics chip with 32 MB external DDR SGRAM Video RAM
<i>Sound capabilities</i>	16-bit CD-quality stereo sound

**Model name****PCG-NV209**

<p><i>CD-ROM drive</i> <i>DVD-ROM drive</i> <i>CD-RW drive</i></p>	<p>CD-RW/DVD-ROM drive: up to 24x max. CD-ROM reading speed up to 16x max. CD-R writing speed up to 10x max. CD-RW writing speed up to 8x max. DVD-ROM reading speed</p> <p>laser diode properties: wave length: DVD 650 nm / CD-RW 780 nm laser output: DVD 1.28 μW / CD-RW 64 μW</p>
<p><i>Internal modem</i></p>	<p>Built-in V.90/K56Flex (56kbps) data/fax modem</p>
<p><i>Telecommunication capabilities</i></p>	<p>Ethernet network, PSTN data connectivity</p>
<p><i>Expansion capabilities</i></p>	<p>1 x PC Card type III Card 2 x PC Card type II Card 2 x PC Card type I Card and CardBus support</p>
<p><i>Built-in capabilities</i></p>	<p>Stereo speakers, touchpad, Jog Dial™, MagicGate Memory Stick™ slot</p>
<p><i>Special buttons</i></p>	<p>Jog Dial™</p>
<p><i>Connection capabilities on notebook</i></p>	<p>Phone line, i.LINK™ (IEEE1394) S400, 3 x USB, Ethernet network (LAN), monitor (VGA), parallel port, serial port, external speakers or headphone, microphone, AV mini jack (for computer out and line out), 1 x PC Card type III Card, 2 x PC Card type II Card, 2 x PC Card type I Card, DC In (AC adapter), MagicGate Memory Stick™</p>
<p><i>Supplied accessories</i></p>	<p>Rechargeable battery, AC adapter, AC power cord, phone cable, 3.5" floppy disk drive bay unit, ten-key bay unit, phone plug</p>

Model name**PCG-NV209**

<i>Power source</i>	80 watts max. (19.5V DC/AC100-240V)
<i>Power management</i>	ENERGY STAR® compliant ACPI (Advanced Configuration & Power Interface)
<i>Battery</i>	Lithium ion
<i>Dimensions</i>	
<i>Width</i>	336 mm
<i>Height</i>	42.8 to 53.3 mm
<i>Depth</i>	276.1 mm
<i>Weight</i>	
<i>With 1 battery</i>	3.7 kg
<i>Weight</i>	
<i>With 1 battery and 3.5" Floppy Disk Drive Bay unit</i>	3.9 kg
<i>Operating temperature</i>	+5°C to +35°C (temperature gradient less than 10°C/hour)
<i>Storage temperature</i>	-20°C to +60°C (temperature gradient less than 10°C/hour)
<i>Operating humidity</i>	20% to 80% (not condensed), provided that humidity is less than 65% at +35°C (hygrometer reading of less than +29°C)
<i>Storage humidity</i>	10% to 90% (not condensed), provided that humidity is less than 20% at +60°C (hygrometer reading of less than +35°C)

Specifications are subject to change without notice.


PCG-NV309

Model name

PCG-NV309

<i>Model number</i>	PCG-9C4M
<i>Operating system</i>	Microsoft® Windows® XP Home Edition
<i>Processor</i>	AMD Mobile Athlon™ XP processor 2000+ featuring PowerNow!™ Technology
<i>Hard disk drive</i>	30 GB
<i>Standard RAM</i>	256 MB DDR (in slot)
<i>Maximum RAM</i>	1 GB
<i>LCD screen</i>	15.0" XGA (1024x768) TFT screen
<i>L2 cache memory</i>	256 KB (on die)
<i>MPEG</i>	MPEG 2 Digital Video supports full-screen playback
<i>Graphics</i>	NVIDIA® GeForce4™ 420 Go graphics chip with 32 MB external DDR SGRAM Video RAM
<i>Sound capabilities</i>	16-bit CD-quality stereo sound

Model name	PCG-NV309
<p><i>CD-ROM drive</i> <i>DVD-ROM drive</i> <i>CD-RW drive</i></p>	<p>CD-RW/DVD-ROM drive: up to 24x max. CD-ROM reading speed up to 16x max. CD-R writing speed up to 10x max. CD-RW writing speed up to 8x max. DVD-ROM reading speed</p> <p>laser diode properties: wave length: DVD 650 nm / CD-RW 780 nm laser output: DVD 1.28 μW / CD-RW 64 μW</p>
<i>Internal modem</i>	Built-in V.90/K56Flex (56kbps) data/fax modem
<i>Telecommunication capabilities</i>	Ethernet network, PSTN data connectivity
<i>Expansion capabilities</i>	<p>1 x PC Card type III Card 2 x PC Card type II Card 2 x PC Card type I Card and CardBus support</p>
<i>Built-in capabilities</i>	Stereo speakers, touchpad, Jog Dial™, MagicGate Memory Stick™ slot
<i>Special buttons</i>	Jog Dial™
<i>Connection capabilities on notebook</i>	Phone line, i.LINK™ (IEEE1394) S400, 3 x USB, Ethernet network (LAN), monitor (VGA), parallel port, serial port, external speakers or headphone, microphone, AV mini jack (for computer out and line out), 1 x PC Card type III Card, 2 x PC Card type II Card, 2 x PC Card type I Card, DC In (AC adapter), MagicGate Memory Stick™
<i>Supplied accessories</i>	Rechargeable battery, AC adapter, AC power cord, phone cable, 3.5" floppy disk drive bay unit, ten-key bay unit, phone plug

**Model name****PCG-NV309**

<i>Power source</i>	80 watts max. (19.5V DC/AC100-240V)
<i>Power management</i>	ENERGY STAR® compliant ACPI (Advanced Configuration & Power Interface)
<i>Battery</i>	Lithium ion
<i>Dimensions</i> <i>Width</i> <i>Height</i> <i>Depth</i>	336 mm 42.8 to 53.3 mm 276.1 mm
<i>Weight</i> <i>With 1 battery</i>	3.7 kg
<i>Weight</i> <i>With 1 battery and 3.5"</i> <i>Floppy Disk Drive Bay unit</i>	3.9 kg
<i>Operating temperature</i>	+5°C to +35°C (temperature gradient less than 10°C/hour)
<i>Storage temperature</i>	-20°C to +60°C (temperature gradient less than 10°C/hour)
<i>Operating humidity</i>	20% to 80% (not condensed), provided that humidity is less than 65% at +35°C (hygrometer reading of less than +29°C)
<i>Storage humidity</i>	10% to 90% (not condensed), provided that humidity is less than 20% at +60°C (hygrometer reading of less than +35°C)

Specifications are subject to change without notice.